



MALTESE CROSS MIRRORS

1425

FITS: UNIVERSAL APPLICATIONS

PARTS INCLUDED

- 1 Left Maltese Mirror Assembly
- 1 Right Maltese Mirror Assembly
- 1 Hardware Kit Including:
 - 2 5/16-18 x 1-1/2" SHCS Fastener
 - 2 5/16-18 x 2" SHCS Fastener
 - 2 5/16-18 x 5/16-24 Double-ended Stud
 - 4 5/16" Internal Tooth Lock Washer
 - 4 5/16" Split Lock Washer
- 1 Installation Instruction

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

PLEASE NOTE

It is the installers' responsibility to make sure all fasteners (including pre-assembled) are tightened before operation of motorcycle. Kuryakyn will not warranty components that are lost due to improper installation. Periodic maintenance may be required.

NOTE

Metric cruisers will require mirror adapters; P/N 1445 for Honda, Suzuki, Kawasaki, Victory and P/N 1446 for Yamaha. You will have left over hardware on some installations. A variety of hardware is included to accommodate a variety of styles of H-D controls as well as some "universal" applications.

TOOLS SUGGESTED

Set of Standard Combination Wrenches, Set of Allen Wrenches and Red Loctite,

PROCEDURE

STEP 1 Remove existing mirrors from your bike. Pay attention to the order in which you remove these components. This will help you reassemble.

RIGHT SIDE

STEP 2 This part of the procedure applies to Harley-Davidson models using the swivel mount on the right handle bar. Any others should skip to the LEFT SIDE installation as the procedure will be the same for both sides.

- A.** Place a drop of red loctite on the short section of threads on the mounting stud. Thread this section into the threaded hole on the bottom of the right side mirror stem and tighten.

NOTE Ensure that the setscrew in the mirror stem does not prevent the stud from being fully installed. See [PIC.1](#).

-cont.-

CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA All Rights reserved.



- B.** Place a star washer on the remaining section of threads (where the stud will rest on the hand control) and insert this assembly into the hand control. Secure this assembly in place with the “cupped” portion of the universal joint. Connect the remainder of the ball joint assembly. Hold the turn signal in place and tighten the ball joint locking it into position. (This assembly is to be reassembled in reverse order of disassembly.)
- C.** Tighten the setscrew to help prevent the stem from moving out of position. See [PIC.1](#).

LEFT SIDE

STEP 3 Test fit the two lengths of bolts included in the kit on your hand controls. Use the bolt (with split lock washers) that provides the most thread engagement without bottoming out in the mirror stem. (Use the 2” long bolts on '82 and newer H-D models.) Insert the bolt through the turn signal mounting plate and hand control from the bottom up on the hand control. Place a star washer over the exposed length of threads and tighten the mirror stem.

NOTE Ensure that the setscrew in the mirror stem does not prevent the stud from being fully installed. See [PIC.1](#).

STEP 4 Adjust the mirrors for maximum rearward visibility. A 5/16” open end wrench may be used to tighten the mirror head to the stem.

STEP 5 Tighten the setscrew to help prevent the stem from moving out of position. See [PIC.1](#).

Ride On!

PIC.1

