



Revision: 1.0 - 02/19/2010

INCLUDED IN THE KIT:

(1) - Chrome Triple Tree Cover	
---------------------------------------	--

INSTRUCTIONS:

NOTE: We recommend the use of Blue Loctite on all fasteners and mounting hardware

- **Remove fuel tank or cover it to protect from damage.**
- **Disconnect throttle lines from right grip.**
- **Disconnect front brake line from right master cylinder. *Use caution - brake fluid will damage paint!***
- **Disconnect clutch line from left master cylinder. *Use caution - brake fluid will damage paint!***
- **Remove nuts that hold the risers to the upper triple tree - they are under the triple tree.**
- **Remove handlebars/risers from triple tree and lay handlebars on the protected tank.**
- **Place new cover on top of triple tree and feed cables and hoses through the provided holes.**
- **Replace riser/handlebar assembly onto upper tree and secure with stock nuts and washers.**
- **Reconnect throttle lines and check for good throttle snap-back.**
- **Reconnect clutch and brake hoses and bleed both systems per Kawasaki shop manual.**
- **Check brakes, clutch and throttle for proper operation before riding the motorcycle.**

Our install guides provide a basic outline on the proper installation of our products. Further tuning and/or fitment may be required. Barons bears no responsibility on installation costs associated with this product.

© 2026 Barons Custom Accessories